

APPM4720/5720 — Homework 3

Everyone should do Problem 3.1. Then you have a choice to do *either* 3.2 and 3.3 *or* 3.4 *or* 3.5.

Problem 3.1: The objective of this problem is to computationally investigate the error incurred by truncating multipole expansions. Consider the following geometry: Let Ω_τ and Ω_σ be two well-separated boxes with centers \mathbf{c}_τ and \mathbf{c}_σ . Let $\mathbf{x} \in \Omega_\sigma$ be a source point and let $\mathbf{y} \in \Omega_\tau$ be a target point. Consider the error function

$$e(P) = \sup \left\{ \left| \log |\mathbf{x} - \mathbf{y}| - \mathbf{B}_P(\mathbf{x}, \mathbf{c}_\tau) \mathbf{Z}_P(\mathbf{c}_\tau, \mathbf{c}_\sigma) \mathbf{C}_P(\mathbf{c}_\sigma, \mathbf{y}) \right| : \mathbf{x} \in \Omega_\sigma \mathbf{y} \in \Omega_\tau \right\}$$

where P is the length of the multipole expansion, and where

$\mathbf{C}_P(\mathbf{c}_\sigma, \mathbf{y}) \in \mathbb{C}^{(P+1) \times 1}$	maps a source to an outgoing expansion
$\mathbf{Z}_P(\mathbf{c}_\tau, \mathbf{c}_\sigma) \in \mathbb{C}^{(P+1) \times (P+1)}$	maps an outgoing expansion to an incoming expansion
$\mathbf{B}_P(\mathbf{x}, \mathbf{c}_\tau) \in \mathbb{C}^{1 \times (P+1)}$	maps an incoming expansion to a target

- (a) Estimate $e(P)$ experimentally for the geometry:

$$\Omega_\sigma = [-1, 1] \times [-1, 1], \quad \Omega_\tau = [3, 5] \times [-1, 1].$$

- (b) Fit the function you determined in (a) to a curve $e(P) \sim c \cdot \alpha^P$. What is α ?
(c) Is the supremum for a given P attained for any specific pair $\{\mathbf{x}, \mathbf{y}\}$?
If so, find (experimentally) the pair. Does the choice depend on P ?
(d) Repeat questions (a), (b), (c) for a different geometry of your choice. (Provide a picture.)
(e) (Optional) Can you support your observations with analysis?

Hint: The provided file `main_T_ops_are_fun.m` might be useful.

Problem 3.2: The objective of this exercise is to familiarize yourself with the provided prototype FMM. The questions below refer to the basic FMM provided in the file `main_fmm.m` when executed on a uniform particle distribution. For this case, precompute only the translation operators $T^{(ofo)}$, $T^{(ifo)}$, and $T^{(ifi)}$ (i.e. set `flag_precomp=0`).

- (a) Estimate and plot the execution time of the FMM for the choices

$$N_{\text{tot}} = 1\,000, 2\,000, 4\,000, 8\,000, 16\,000, 32\,000, 64\,000.$$

Set `nmax=50`. Provide plots that track the following costs:

t_{tot}	total execution time, including initialization.
t_{init}	cost of initialization (computing the tree, the object <code>T_OPS</code> , etc.).
t_{ofs}	cost of applying $T^{(\text{ofs})}$.
t_{ofo}	cost of applying $T^{(\text{ofo})}$.
t_{ifo}	cost of applying $T^{(\text{ifo})}$.
t_{ifi}	cost of applying $T^{(\text{ifi})}$.
t_{tfi}	cost of applying $T^{(\text{tfi})}$.
t_{close}	cost of directly evaluating close range interactions.

- (b) Repeat exercise (a) but now for a few different choices of `nmax`. Which one is the best one? Provide a new plot of the times required for this optimal choice.

Problem 3.3: Repeat Problem 3.2 but now use a non-uniform point distribution of your choice.

Problem 3.4: Can you think of a better way of computing the interaction lists? Here “better” could mean either a cleaner code that executes in more or less the same time, or a code that executes significantly faster than the provided one. If your code is **both** cleaner and faster then so much the better!

Problem 3.5: Code up the single-level Barnes-Hut method and investigate computationally how many boxes you should use for optimal performance for any given precision and given total number N_{tot} of charges. Create a plot of the best possible time t_{optimal} for several N_{tot} and estimate the dependence of t_{optimal} on N_{tot} . To keep things simple, consider only uniform particle distributions. You need only consider a fixed precision (say $P = 10$) but an ambitious solution should compute the optimal time for several different choices (say $P = 5, 10, 15, 20$).